

Braunschweig Civil Engineering Materials Testing Institute (MPA Braunschweig)

Beethovenstr. 52, DE-38106 Braunschweig, Germany Tel: ++49(0)531-391-5400 Fax: ++49(0)531-391-5900 Email: <u>info@mpa.tu-bs.de</u> Website : www.mpa.tu-bs.de

This certificate of compliance validates the following

TEST REPORT NUN DATE OF ISSUE: DATE OF EXPIRY:	/IBER:	3490/732/14 2014-07-22 N/A	DATE	ICATE NUMBER: DF ISSUE: DF EXPIRY:	MPA BS-Z-053/17 2022-07-19 2027-07-20
A/ FACTORY IN		NCO Building & Industry STRIVEJ 22 00 NAESTVED	NAME OF THE BRAND: MODEL/NO: LOGO ON THE PRODUCT:	NOVENCO NOVAX Type AUP/ Dia. 340mm Class F300	CERTIFICATION MARK: Z-053/17
	Denmark Tel: +45 7077 88 99 Email: info@novenco- building.com			NOVENO SCHAKO	
DESCRIPTION OF THE PRODUCT:	Powered jet fans for car parks and tunnels including the removal of smoke at high temperatures, i.e. for operation at 300°C for a minimum of 120 minutes.				
TEST STANDARD: TEST DESCRIPTION:	EN 12101-3 A jet fan with a diameter of 340 mm was tested in a horizontal position for 126 min in an oven heated up to 400°C by means of gas burners. Temperature measurements were done with thermocouples. During the test, temperature, volume flow, pressure and electrical values (current, voltage, etc) were measured. The test standard requires to stop the operation after 15 min for two minutes and to restart it.				
SPECIFICATION OF TEST SPECIMEN:	The jet fan tested had a diameter of 340 mm with a power input of 1.3 kW. It was equipped with silencers.				
TEST RESULT:	I NAME OF TAXABLE PARTY.	NANCE OF FUNCTION DR 120 MIN	INTERPRETA SUCCESSFUL	TION RESULT PASSED	
NAME OF TEST FACILITY: TEST FACILITY ADDRESS/REGION: PRODUCT	MPA Braunschweig Beethovenstr. 52, D-38106 Braunschweig Tel: ++49(0) 531 391 5400, Fax: ++49(0) 531 391 5900 Email: info@mpa.tu-bs.de, Website: www.mpa-tu-bs.de For use as a powered smoke and heat jet fans for temperatures up to 300°C and for up to 120min in a				
APPLICATION GUIDELINE (END USE): SIGNED BY:	horizontal position inside or outside the fire zone without thermal insulation. The jet fan can be used for dual operation (normal ventilation and hot smoke removal). The product must be applied in accordance with the provisions in the manufacturer's manual. Prior to installation the personnel must be instructed. The above certificate is valid only when installed in accordance with the 'Product Application Guideline (End Use)'. To verify the validity of the product please log into our website, click on 'certification' and then on 'list of certificates'. You will Head of certification and a list of manufacturers and a certificate with the number as given above. PAGE 1 OF 2				



Braunschweig Civil Engineering Materials Testing Institute (MPA Braunschweig)

Beethovenstr. 52, DE-38106 Braunschweig, Germany Tel: ++49(0)531-391-5400 Fax: ++49(0)531-391-5900 Email: <u>info@mpa.tu-bs.de</u> Website : www.mpa.tu-bs.de

Schweig

ACCREDITED BY:	DAkkS
AS PER:	ISO/IEC 17065
VALIDITY:	N/A
REFERENCE NUMBER:	D-ZE-11267-01

DAkkS ISO/IEC 17025 N/A D-PL-11267-01-02

THE LIST OF ACCREDITED TESTS (FIRE AND LIFE SAFETY PRODUCTS ONLY)

TEST STANDARD	TITLE
EN 12101-1	Smoke and heat control systems –
	Part 1: Specification for smoke barriers
EN 12101-2	Smoke and heat control systems –
	Part 2: Specification for natural smoke and heat exhaust ventilators
EN 12101-3	Smoke and heat control systems –
	Part 3: Specification for powered smoke and heat exhaust ventilators
EN 12101-6	Smoke and heat control systems –
	Part 6: Specification for pressure differential systems, Kits
EN 12101-7	Smoke and heat control systems –
	Part 7: Smoke duct sections
EN 12101-8	Smoke and heat control systems –
	Part 8: Smoke control dampers
EN 1366-8	Fire resistance tests for service installations –
	Part 8: Smoke extraction ducts
EN 1366-9	Fire resistance tests for service installations –
	Part 9: Single compartment smoke extraction ducts
EN 1366-10	Fire resistance tests for service installations -
	Part 10: Smoke control dampers
EN 13501-4	Fire classification of construction products and building elements –
	Part 4: Classification using data from fire resistance tests on components of smoke control systems
	END OF PAGE 2 OF 2