

Braunschweig Civil Engineering Materials Testing Institute (MPA Braunschweig)

Beethovenstr. 52, DE-38106 Braunschweig, Germany Tel: +49(0)531-391-5400 Fax: +49(0)531-391-5900 Email: info@mpa.tu-bs.de Website: www.mpa.tu-bs.de

This certificate of compliance validates the following

| TEST REPORT NUI DATE OF ISSUE: DATE OF EXPIRY: | MBER: | 3782/045/07 2010-01-26 N/A | | CERTIFICATE DATE OF ISS DATE OF EXF | UE: | MPA BS-Z-066/17 2022-11-24 2027-11-23 |
|--|---|-----------------------------------|------------------------------------|---|--------------------------|---|
| NAME OF FACTORY/ MANUFACTURER: | NOVENCO Building & Industry A/S | | NAME OF THE BRAND: MODEL/NO: | | vpe ARN 1m – 1,600 mm | Z-066/17 |
| FACTORY ADDRESS/REGION: | DK-4700 Denmar Tel: +45 | 7077 88 99 nfo@novenco- | LOGO ON THE PRODUCT: | Building & Inc | lustry | ZERTIFIZIERT IBMBWPA |
| DESCRIPTION OF THE PRODUCT: | Powered axial flow fans for use in industrial ventilation including the removal of smoke at high temperatures, i.e. for operation at 300 °C for a minimum of 120 minutes. | | | | | |
| TEST STANDARD: TEST DESCRIPTION: | EN 12101-3 Four ventilators were tested in an oven heated up to 300 °C by means of gas burners. Temperature measurements were done with thermocouples. During the test, temperature, volume flow, pressure and electrical values (current, voltage, etc) were measured. The test standard requires to stop the operation after 15 min for two minutes and to restart it. | | | | | |
| SPECIFICATION OF TEST SPECIMEN: | The axial flow fan tested had diameter of 1,600 mm with a power input of 45 kW. It was equipped with silencers. | | | | | |
| TEST RESULT: | | NANCE OF FUNCTIO DR 120 MIN | | RPRETATION ESSFUL | RESULT PASSED | |
| NAME OF TEST FACILITY: TEST FACILITY | | unschweig enstr. 52. D-38106 B | raunschweig | | | |
| ADDRESS/REGION: PRODUCT APPLICATION GUIDELINE (END USE): | Beethovenstr. 52, D-38106 Braunschweig Tel: +49(0) 531 391 5400, Fax: +49(0) 531 391 5900 Email: info@mpa.tu-bs.de, Website: www.mpa-tu-bs.de For use as a powered smoke and heat ventilators for temperatures up to 300 °C and for up to 120 min in a horizontal or a vertical position inside or outside the fire zone without thermal insulation. The ventilator can be used for dual operation (normal ventilation and hot smoke removal). The product must be applied in accordance with the provisions in the manufacturer's manual. Prior to installation the personnel must be instructed. | | | | | |
| SIGNED BY: | The above certificate is valid only when installed in accordance with the 'Product Application Guideline (E Use)'. To verify the validity of the product please log i our website, click on 'certification' and then on 'list of certificates'. You will find a list of manufacturers and a certificate with the number as given above. | | | | | duct Application Guideline (End y of the product please log into ification' and then on 'list of a list of manufacturers and a |
| | Head of certification | | | | | |



Braunschweig Civil Engineering Materials Testing Institute (MPA Braunschweig)

Beethovenstr. 52, DE-38106 Braunschweig, Germany Tel: +49(0)531-391-5400 Fax: +49(0)531-391-5900 Email: info@mpa.tu-bs.de Website: www.mpa.tu-bs.de

| ACCREDITED BY: | DAkkS |
|--------------------------|------------------|
| AS PER: | ISO/IEC 17065 |
| VALIDITY: | N/A |
| REFERENCE NUMBER: | D-ZE-11267-01-00 |

DAkkS ISO/IEC 17025 N/A D-PL-11267-01-02

THE LIST OF ACCREDITED TESTS (FIRE AND LIFE SAFETY PRODUCTS ONLY)

| TEST STANDARD | TITLE |
|---------------|---|
| EN 12101-1 | Smoke and heat control systems – |
| | Part 1: Specification for smoke barriers |
| EN 12101-2 | Smoke and heat control systems – |
| | Part 2: Specification for natural smoke and heat exhaust ventilators |
| EN 12101-3 | Smoke and heat control systems – |
| | Part 3: Specification for powered smoke and heat exhaust ventilators |
| EN 12101-6 | Smoke and heat control systems – |
| | Part 6: Specification for pressure differential systems, Kits |
| EN 12101-7 | Smoke and heat control systems – |
| | Part 7: Smoke duct sections |
| EN 12101-8 | Smoke and heat control systems – |
| | Part 8: Smoke control dampers |
| EN 1366-8 | Fire resistance tests for service installations – |
| | Part 8: Smoke extraction ducts |
| EN 1366-9 | Fire resistance tests for service installations – |
| | Part 9: Single compartment smoke extraction ducts |
| EN 1366-10 | Fire resistance tests for service installations – |
| | Part 10: Smoke control dampers |
| EN 13501-4 | Fire classification of construction products and building elements – |
| | Part 4: Classification using data from fire resistance tests on components of smoke control systems |

